

## HIGH PERFORMANCE SOLUTIONS

# G20

- 900 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- 20 printheads
- Very precise printing, perfectly clear output
- Robust Structure



Printing Speed

**900** m<sup>2</sup>/sa

Printing Width

**190** cm  
'up to'



KARYA Dijital

**K//AN**  
DIGITAL

**J**  
TECK

*inēdit*

**CALDERA**  
WIDE FORMAT IMAGING

**ergosoft**  
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.  
No: 22 Merter - Güngören / İstanbul - Turkey  
P +90 212 637 03 34

BURSA

Panayır Mahallesi 3. Pınar Caddesi No:265  
Osmangazi- Bursa - Turkey  
P +90 224 211 45 79

[www.karyadijital.com](http://www.karyadijital.com)

[sales@karyadijital.com](mailto:sales@karyadijital.com)


[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Steel beam & rail longer life and more stable
- Linear motor higher print speed



- Epson i3200 printhead
- 64,000 nozzles in total



- Excellent printing precision
- Outstanding performance



- Patented special design, no wrinkle paper
- Continuous pinch roller design to prevent uneven paper




- Independent cleaning station for each head
- Longitudinal Ink Squeegee better protect of printhead
- Independent pump for each print head



- Robust Structure
- 15,000m jumbo system

## TECHNICAL PROPERTIES

Model	G20	 <p>SCAN FOR PACKING DETAILS</p>
Print Head	20 * EPSON i3200	
Maximum Print Width	1900mm	
Motor	Linear motor	
Ink Type	Dye Sublimation Ink, Graphic pigment Ink	
Number of Colors	4 colors, 8 colors (Optional)	
Printing Speeds	360 x 1200 – 1 pass 900 m <sup>2</sup> /h	
	360 x 1800 – 1 pass 820 m <sup>2</sup> /h	
	720 x 1200 – 2 pass 410 m <sup>2</sup> /h	
Maximum Media Load	T7 Jumbo system: max. feeding 15,000m paper roll (30g)	
RIP Software	MainTop / ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Supply	Total power: 17.2 kW	
Ink Tank	Big Ink Supply system, 25L/tank	
Operation system	windows – 64 bit system	
Net Dimensions (LxWxH)	4550x3050x2440 mm	