

## **HIGH PERFORMANCE SOLUTIONS**



- 160 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- **Outstanding price/performance ratio** for its epson i3200 heads
- n.3 printheads
- Very precise printing, perfectly clear output
- **Robust Structure**



## **Printing Speed**



## **Printing Width**





















- Mimimum drop size 2 pl
- n.3 staggered epson i3200 printhead
- n. 3200 nozzles per head,
  n. 9600 nozzles in total.



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.



 From suction system to dampers, filtration system to electronics, many innovative approach & relative patents.



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels.



Special design patented2 stage ink feeding system.

## **TECHNICAL PROPERTIES**

Print Head	n.3 on-demand Piezo / staggered	回経回
Maximum Print Width	1900mm	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink	
Number of Colors	4 colors, 6 colors (Optional)	SCAN FOR PACKING DETAILS
Ink Feeding System	Open bulk system with 20 µm filter	
Media	Weight: up to 20 kg	
	Lenght: 200 – 300 mm	
	Roll Diameter: 50 mm – 75 mm	
	360 x 1200 - 2 pass 160 m²/h	
Printing Speeds	360 x 1800 - 3 pass 120 m²/h	
	720 x 1200 - 4 pass 80 m²/h	
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Consumption	300 W or less (except drying unit)	
Net Dimensions (LxWxH)	3350x950x1970 mm	